



PRODUCT CARD

ISWX+ E2

2-GLAZED ROOF WINDOW WOODEN



INTENDED USE

in roofs with a pitch of 15°-65°

window designed for communication in residential and commercial locations

recommended for unheated attics

MATERIAL

pine wood impregnated and painted with colourless eco-friendly varnish

FEATURES

2-glazed package

excellent thermal insulation

door handle with two keys as standard

ventilation option thanks to the micro-opening function in the handle

exceptional tightness thanks to four seals

enables safe access to the roof

the pivot point at the top of the sash allows it to open up to 180°

equipped with actuators supporting smooth opening of the sash within a range of up to 30°

AKP vapour-permeable collar as standard

can be installed with additional sealing accessories (UTB)

WINDOW PANE

construction E2 4ESG/16/4TF

window package 24 mm

low-emission coating ■

gas argon

internal laminated glass -

external tempered glass ■

warm spacer bar ■

heat transfer coefficient of glass $U_g = 1,0 \text{ W/m}^2\text{K}$

WINDOW

window heat transfer coefficient $U_w = 1,2 \text{ W/m}^2\text{K}$

water resistance E1050

air permeability Class 4

wind load resistance Class C3

acoustic properties $R_w = 32 \text{ dB}$

impact resistance Class 3

load capacity of safety devices 350N

COLOUR

wood natural

cladding anthracite RAL 7016

AVAILABLE DIMENSIONS

| glazing area [m ²] | 0,21 | 0,28 | 0,36 | 0,46 |
|----------------------------------|-------|-------|-------|-------|
| window size: width x height [cm] | 55x78 | 55x98 | 66x98 | 78x98 |
| ISWX+ E2 | ✓ | ✓ | ✓ | ✓ |